

VACUUM



Air &
Multipurpose
General Purpose
Heavy Duty
Push-on

Chemical
Transfer

Cleaning
Equipment

Food
Transfer
Washdown

Marine

Material Handling

Abrasives
Bulk Transfer
Cement & Concrete

Mining

Petroleum
Aircraft Fueling
Dispensing
Dock
Transfer

Spray

Steam

Vacuum

Water
Discharge
Suction &
Discharge
Washdown

Welding

Coupling
Systems

Appendix
Additional
Products
Chemical Charts
General
Information
Minimum Run
Requirements

APPLICATION: For lawn, leaf, mulch and yard waste collection. It is also suitable for dust control, ventilation, and ducting.

CONSTRUCTION TUBE: Clear Pliovic™

REINFORCEMENT: Black rigid, high-density Pliovic helix

TEMPERATURE: 0°F to 158°F (-18°C to 70°C)

PACKAGING: 4–6" 100' lengths, coiled and polywrapped
7–8" 50' lengths, coiled and polywrapped

BRANDING: Not branded

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

NON-STOCK/SIZES: Available in all black construction.

ORDER CODES: 586-429 (clear web, black helix)

ID		NOM. OD		MAX. WP		BEND RADIUS		VACUUM HG		WEIGHT	
in.	mm.	in.	mm.	psi	Mpa	in.	mm.	in.	mm.	lb./ft.	kg./m.
4	101.6	4.46	113.3	15	0.10	4	102	15	381	0.71	1.06
5	127.0	5.55	141.0	15	0.10	7	178	15	381	1.07	1.59
6	152.4	6.56	166.6	10	0.07	7	178	15	381	1.43	2.13
7	177.8	7.63	193.8	10	0.07	9	229	15	381	1.75	2.60
8	203.2	8.66	220.0	10	0.07	9	229	15	381	2.06	3.07

See Page 2 for complete product warranty and terms of sale information. In V-Cat, please reference the Conditions of Sale page in the General Information section. Information in this catalog supersedes all previously printed material. Information valid as of the day published. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online at www.goodyear.com.

© 2007 The Goodyear Tire & Rubber Company.