

Gauntlet® 4500

APPLICATION:

For use on pressure washer machines with working pressures up to 4500 psi. Its super abrasion-resistant cover provides maximum protection against adverse affects of oil and animal fats.



CONSTRUCTION:

TUBE: Nitrile synthetic rubber

COVER: Black or Yellow oil-resistant Carbryn® synthetic rubber, RMA Class A (High Oil Resistance)

REINFORCEMENT: Braided (2) steel wires

TEMPERATURE: -20°F to 250°F (-29°C to 121°C)

PACKAGING: 1/4"-3/8" 500' reels, maximum 3 pieces, minimum of 50'lengths, coupled lengths available / 1/2" 500' reels, maximum 3 pieces, minimum of 50'lengths, coupled lengths available

BRANDING: Continuous brand "Goodyear™ Gauntlet 4500 3/8" 4500 psi WP. Made in USA."

COUPLINGS: Use Goodyear's powerwash fittings with this product. See page 235 for available sizes. Refer to Goodyear's Hose Assembly Manual for crimp procedures. Coupled lengths with MxMS fittings and Kink Guards available.

NON-STOCK/SIZES: Refer to page 300 for special production run minimum requirements.

ORDER CODES: 539-122 (black) / 539-120 (yellow)

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi	Mpa	lb./ft.	kg./m.
1/4	6.4	0.54	13.7	4500	31.03	0.20	0.30
3/8	9.5	0.69	17.5	4500	31.03	0.28	0.42
1/2	12.7	0.82	20.8	4500	31.03	0.35	0.52

Note: Not recommended for steam service.

The GOODYEAR (and Winged Foot Design) trademark is used by Veyance Technologies, Inc. under license from The Goodyear Tire & Rubber Company.

Goodyear Engineered Products are manufactured and sourced exclusively by Veyance Technologies, Inc. or its affiliates.

©2008 Veyance Technologies, Inc. All Rights Reserved.