

WATER DISCHARGE

PATHFINDER® GARDEN HOSE



Air &
Multipurpose
General Purpose
Heavy Duty
Push-on

Chemical
Transfer

Cleaning
Equipment

Food
Transfer
Washdown

Marine

Material Handling
Abrasives
Bulk Transfer
Cement & Concrete

Mining

Petroleum
Aircraft Fueling
Dispensing
Dock
Transfer

Spray

Steam

Vacuum

Water
Discharge
High Pressure
High Velocity
Industrial

Welding

Coupling
Systems

Appendix
Additional
Products
Chemical Charts
General
Information
Minimum Run
Requirements

APPLICATION: For in-home, lawn and garden, apartment, smaller plant and commercial property applications.

CONSTRUCTION
TUBE: Versigard® synthetic rubber
COVER: Green Versigard synthetic rubber
REINFORCEMENT: Spiral synthetic yarn

TEMPERATURE: -40°F to 190°F (-40°C to 88°C)

PACKAGING: 500' reels, maximum 3 pieces, 50' increments

BRANDING: Continuous brand example 5/8" (15.9 mm) Pathfinder by Goodyear™ 100 psi WP.

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

NON-STOCK/SIZES: Available in 25' or 50' coupled assemblies.

ORDER CODES: 569-027

ID		NOM. OD		MAX. WP		WEIGHT	
<i>in.</i>	<i>mm.</i>	<i>in.</i>	<i>mm.</i>	<i>psi.</i>	<i>Mpa.</i>	<i>lb./ft.</i>	<i>kg./m.</i>
5/8	15.9	0.94	23.9	100	0.69	0.22	0.33

See Page 2 for complete product warranty and terms of sale information. In V-Cat, please reference the Conditions of Sale page in the General Information section. Information in this catalog supersedes all previously printed material. Information valid as of the day published. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online at www.goodyearrep.com.

© 2007 The Goodyear Tire & Rubber Company.