

ABRASIVES



- APPLICATION:** Heavy-duty hose for steel shot or sand blasting in cleaning or finishing metal, stone, glass or other surfaces.
- CONSTRUCTION**
- TUBE:** Tufsyn® synthetic rubber (static dissipating/static conductive)
- COVER:** 2 ply: Black Plioflex® synthetic rubber (wrapped impression)
4 ply: Green Plioflex synthetic rubber (wrapped impression)
- REINFORCEMENT:** Spiral-plyed synthetic fabric
- TEMPERATURE:** -25°F to 180°F (-32°C to 82°C)
- PACKAGING:** 50' lengths, coiled and polywrapped
- BRANDING:** Spiral brand Goodyear™ Plicord Blast 150 psi WP.
- COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.
- NON-STOCK/SIZES:** Refer to page 300 for special production run minimum requirements.

PLICORD BLAST (2 PLY)

ORDER CODES: 549-020

| ID | | NOM. OD | | MAX. WP | | WEIGHT | |
|-------|------|---------|------|---------|------|---------|--------|
| in. | mm. | in. | mm. | psi. | Mpa. | lb./ft. | kg./m. |
| 1/2 | 12.7 | 1.13 | 28.7 | 150 | 1.03 | 0.41 | 0.61 |
| 3/4 | 19.1 | 1.48 | 37.6 | 150 | 1.03 | 0.68 | 1.01 |
| 1 | 25.4 | 1.88 | 47.8 | 150 | 1.03 | 1.05 | 1.56 |
| 1 1/4 | 31.8 | 2.16 | 54.9 | 150 | 1.03 | 1.26 | 1.88 |
| 1 1/2 | 38.1 | 2.38 | 60.5 | 150 | 1.03 | 1.42 | 2.11 |
| 2 | 50.8 | 2.86 | 72.6 | 150 | 1.03 | 1.70 | 2.53 |

PLICORD BLAST (4 PLY)

ORDER CODES: 549-027

| ID | | NOM. OD | | MAX. WP | | WEIGHT | |
|-------|------|---------|------|---------|------|---------|--------|
| in. | mm. | in. | mm. | psi. | Mpa. | lb./ft. | kg./m. |
| 1/2 | 12.7 | 1.14 | 26.7 | 150 | 1.03 | 0.44 | 0.61 |
| 3/4 | 19.1 | 1.50 | 38.1 | 150 | 1.03 | 0.71 | 1.06 |
| 1 | 25.4 | 1.88 | 47.8 | 150 | 1.03 | 1.08 | 1.61 |
| 1 1/4 | 31.8 | 2.16 | 54.9 | 150 | 1.03 | 1.31 | 1.95 |
| 1 1/2 | 38.1 | 2.38 | 60.5 | 150 | 1.03 | 1.45 | 2.16 |
| 2 | 50.8 | 2.88 | 73.2 | 150 | 1.03 | 1.75 | 2.60 |

See Page 2 for complete product warranty and terms of sale information. In V-Cat, please reference the Conditions of Sale page in the General Information section. Information in this catalog supersedes all previously printed material. Information valid as of the day published. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online at www.goodyearrep.com.

© 2007 The Goodyear Tire & Rubber Company.

Air &
Multipurpose
General Purpose
Heavy Duty
Push-on

Chemical
Transfer

Cleaning
Equipment

Food
Transfer
Washdown

Marine

Material Handling

Abrasives

Blowdown

Conveyance

Mining

Petroleum
Aircraft Fueling
Dispensing
Dock
Transfer

Spray

Steam

Vacuum

Water
Discharge
Suction &
Discharge
Washdown

Welding

Coupling
Systems

Appendix
Additional
Products
Chemical Charts
General
Information
Minimum Run
Requirements